

What is claimed is:

1. A system for detecting an analyte in a fluid comprising:

5 a light source;

a sensor array, the sensor array comprising a supporting member comprising at least one cavity formed within the supporting member;

10 a particle, the particle positioned within the cavity, wherein the particle is configured to produce a signal when the particle interacts with the analyte during use; and

a detector, the detector being configured to detect the signal produced by the interaction of the analyte with the particle during use;

5 wherein the light source and detector are positioned such that light passes from the light source, to the particle, and onto the detector during use.

20 2. The system of claim 1, wherein the system comprises a plurality of particles positioned within a plurality of cavities, and wherein the system is configured to substantially simultaneously detect a plurality of analytes in the fluid.

25 3. The system of claim 1, wherein the system comprises a plurality of particles positioned within the cavity.

4. The system of claim 1, wherein the light source comprises a light emitting diode.

5. The system of claim 1, wherein the light source comprises a white light source.

30 6. The system of claim 1, wherein the sensor array further comprises a bottom layer and a

top cover layer, wherein the bottom layer is coupled to a bottom surface of the supporting member, and wherein the top cover layer is coupled to a top surface of the supporting member; and wherein both the bottom layer and the top cover layer are coupled to the supporting member such that the particle is substantially contained within the cavity by bottom layer and the top cover layer.

7. The system of claim 1, wherein the sensor array further comprises a bottom layer and a top cover layer, wherein the bottom layer is coupled to a bottom surface of the supporting member, and wherein the top cover layer is coupled to a top surface of the supporting member; and wherein both the bottom layer and the top cover layer are coupled to the supporting member such that the particle is substantially contained within the cavity by bottom layer and the top cover layer, and wherein the bottom layer and the top cover layer are substantially transparent to light produced by the light source.

8. The system of claim 1, wherein the sensor array further comprises a bottom layer coupled to the supporting member, and wherein the supporting member comprises silicon, and wherein the bottom layer comprises silicon nitride.

9. The system of claim 1, wherein the sensor array further comprises a sensing cavity formed on a bottom surface of the sensor array.

10. The system of claim 1, wherein the supporting member is formed from a plastic material, and wherein the sensor array further comprises a top cover layer, the top cover layer being coupled to the supporting member such that the particle is substantially contained within the cavity, and wherein the top cover layer is configured to allow the fluid to pass through the top cover layer to the particle, and wherein both the supporting member and the top cover layer are substantially transparent to light produced by the light source.

11. The system of claim 1, further comprising a fluid delivery system coupled to the

supporting member.

12. The system of claim 1, wherein the detector comprises a charge-coupled device.

5 13. The system of claim 1, wherein the detector comprises an ultraviolet detector.

14. The system of claim 1, wherein the detector comprises a fluorescence detector.

10 15. The system of claim 1, wherein the detector comprises a semiconductor based photodetector, and wherein the detector is coupled to the sensor array.

16. The system of claim 1, wherein the particle ranges from about 0.05 micron to about 500 microns.

5 17. The system of claim 1, wherein a volume of the particle changes when contacted with the fluid.

18. The system of claim 1, wherein the particle comprises a metal oxide particle.

20 19. The system of claim 1, wherein the particle comprises a metal quantum particle.

20. The system of claim 1, wherein the particle comprises a semiconductor quantum particle.

25 21. The system of claim 1, wherein the particle comprises a receptor molecule coupled to a polymeric resin.

22. The system of claim 1, wherein the particle comprises a receptor molecule coupled to a polymeric resin, and wherein the polymeric resin comprises polystyrene-polyethylene glycol-divinyl benzene.

23. The system of claim 1, wherein the particle comprises a receptor molecule coupled to a polymeric resin, and wherein the receptor molecule produces the signal in response to the pH of the fluid.

5

24. The system of claim 1, wherein the particle comprises a receptor molecule coupled to a polymeric resin, and wherein the analyte comprises a metal ion, and wherein the receptor produces the signal in response to the presence of the metal ion.

10

25. The system of claim 1, wherein the particle comprises a receptor molecule coupled to a polymeric resin, and wherein the analyte comprises a carbohydrate, and wherein the receptor produces a signal in response to the presence of a carbohydrate.

15  
20  
25  
30  
35  
40  
45  
50  
55  
60  
65  
70  
75  
80  
85  
90  
95  
100  
105  
110  
115  
120  
125  
130  
135  
140  
145  
150  
155  
160  
165  
170  
175  
180  
185  
190  
195  
200  
205  
210  
215  
220  
225  
230  
235  
240  
245  
250  
255  
260  
265  
270  
275  
280  
285  
290  
295  
300  
305  
310  
315  
320  
325  
330  
335  
340  
345  
350  
355  
360  
365  
370  
375  
380  
385  
390  
395  
400  
405  
410  
415  
420  
425  
430  
435  
440  
445  
450  
455  
460  
465  
470  
475  
480  
485  
490  
495  
500  
505  
510  
515  
520  
525  
530  
535  
540  
545  
550  
555  
560  
565  
570  
575  
580  
585  
590  
595  
600  
605  
610  
615  
620  
625  
630  
635  
640  
645  
650  
655  
660  
665  
670  
675  
680  
685  
690  
695  
700  
705  
710  
715  
720  
725  
730  
735  
740  
745  
750  
755  
760  
765  
770  
775  
780  
785  
790  
795  
800  
805  
810  
815  
820  
825  
830  
835  
840  
845  
850  
855  
860  
865  
870  
875  
880  
885  
890  
895  
900  
905  
910  
915  
920  
925  
930  
935  
940  
945  
950  
955  
960  
965  
970  
975  
980  
985  
990  
995

26. The system of claim 1, wherein the particle comprises a receptor molecule coupled to a polymeric resin, and wherein the particles further comprises a first indicator and a second indicator, the first and second indicators being coupled to the receptor, wherein the interaction of the receptor with the analyte causes the first and second indicators to interact such that the signal is produced.

20

27. The system of claim 1, wherein the particle comprises a receptor molecule coupled to a polymeric resin, and wherein the particles further comprises an indicator, wherein the indicator is associated with the receptor such that in the presence of the analyte the indicator is displaced from the receptor to produce the signal.

25

28. The system of claim 1, wherein the particle comprises a receptor molecule coupled to a polymeric resin, and wherein the receptor comprises a polynucleotide.

29. The system of claim 1, wherein the particle comprises a receptor molecule coupled to a polymeric resin, and wherein the receptor comprises a peptide.

30. The system of claim 1, wherein the particle comprises a receptor molecule coupled to a polymeric resin, and wherein the receptor comprises an enzyme.

5 31. The system of claim 1, wherein the particle comprises a receptor molecule coupled to a polymeric resin, and wherein the receptor comprises a synthetic receptor.

32. The system of claim 1, wherein the particle comprises a receptor molecule coupled to a polymeric resin, and wherein the receptor comprises an unnatural biopolymer.

10

33. The system of claim 1, wherein the particle comprises a receptor molecule coupled to a polymeric resin, and wherein the receptor comprises an antibody.

15

34. The system of claim 1, wherein the particle comprises a receptor molecule coupled to a polymeric resin, and wherein the receptor comprises an antigen.

35. The system of claim 1, wherein the analyte comprises phosphate functional groups, and wherein the particle is configured to produce the signal in the presence of the phosphate functional groups.

20

36. The system of claim 1, wherein the analyte comprises bacteria, and wherein the particle is configured to produce the signal in the presence of the bacteria.

37. The system of claim 1, wherein the system comprises a plurality of particles positioned within a plurality of cavities, and wherein the plurality of particles produce a detectable pattern in the presence of the analyte.

25

38. The system of claim 1, wherein the supporting member comprises silicon.

39. The system of claim 1, wherein the sensor array further comprises a top cover layer, wherein the top cover layer is coupled to a top surface of the supporting member such that the particle is substantially contained within the cavity by the top cover layer.

5 40. The system of claim 1, wherein the sensor array further comprises a bottom layer coupled to the supporting member, and wherein the bottom layer comprises silicon nitride.

41. The system of claim 1, wherein the particles produce a detectable pattern in the presence of the analyte.

10

42. The system of claim 1, wherein the cavity is configured such that the fluid entering the cavity passes through the supporting member during use.

43. The system of claim 1, wherein the light source comprises a red light emitting diode, a blue light emitting diode, and a green light emitting diode.

15

44. The system of claim 1, wherein the sensor array further comprises a cover layer coupled to the supporting member and a bottom layer coupled to the supporting member, wherein the cover layer and the bottom layer are removable.

20

45. The system of claim 1, wherein the sensor array further comprises a cover layer coupled to the supporting member and a bottom layer coupled to the supporting member, wherein the cover layer and the bottom layer are removable, and wherein the cover layer and the bottom layer include openings that are substantially aligned with the cavities during use.

25

46. The system of claim 1, wherein the sensor array further comprises a cover layer coupled to the supporting member and a bottom layer coupled to the supporting member, wherein the bottom layer is coupled to a bottom surface of the supporting member and wherein the cover layer is removable, and wherein the cover layer and the bottom layer include openings that

are substantially aligned with the cavities during use.

47. The system of claim 1, wherein the sensor array further comprises a cover layer coupled to the supporting member and a bottom layer coupled to the supporting member, wherein an opening is formed in the cover layer substantially aligned with the cavity, and wherein an opening is formed in the bottom layer substantially aligned with the cavity.

48. The system of claim 1, wherein the cavity is substantially tapered such that the width of the cavity narrows in a direction from a top surface of the supporting member toward a bottom surface of the supporting member, and wherein a minimum width of the cavity is substantially less than a width of the particle.

49. The system of claim 1, wherein a width of a bottom portion of the cavity is substantially less than a width of a top portion of the cavity, and wherein the width of the bottom portion of the cavity is substantially less than a width of the particle.

50. The system of claim 1, wherein the sensor array further comprises a cover layer coupled to the supporting member and a bottom layer coupled to the supporting member, wherein the bottom layer is configured to support the particle, and wherein an opening is formed in the cover layer substantially aligned with the cavity.

51. The system of claim 1, further comprising a removable cover layer.

52. The system of claim 1, wherein the supporting member comprises a plastic material.

53. The system of claim 1, wherein the supporting member comprises a silicon wafer.

54. The system of claim 1, wherein the supporting member comprises a dry film photoresist material.

55. The system of claim 1, wherein the supporting member comprises a plurality of layers of a dry film photoresist material.

5 56. The system of claim 1, wherein an inner surface of the cavity is coated with a reflective material.

57. The system of claim 1, further comprising channels in the supporting member, wherein the channels are configured to allow the fluid to flow through the channels into and away from  
10 the cavity.

58. The system of claim 1, wherein the sensor array further comprises a pump coupled to the supporting member, wherein the pump is configured to direct the fluid towards the cavity, and wherein a channel is formed in the supporting member, the channel coupling the pump to the cavity such that the fluid flows through the channel to the cavity during use.  
15

59. The system of claim 1, wherein the sensor array further comprises a pump coupled to the supporting member, wherein the pump is configured to direct the fluid towards the cavity, and wherein a channel is formed in the supporting member, the channel coupling the pump to the cavity such that the fluid flows through the channel to the cavity during use, and wherein the pump comprises a diaphragm pump.  
20

60. The system of claim 1, wherein the sensor array further comprises a pump coupled to the supporting member, wherein the pump is configured to direct the fluid towards the cavity, and wherein a channel is formed in the supporting member, the channel coupling the pump to the cavity such that the fluid flows through the channel to the cavity during use, and wherein the pump comprises a diaphragm pump, and wherein the pump comprises an electrode pump.  
25

61. The system of claim 1 wherein the sensor array further comprises a pump coupled to the



supporting member, wherein the pump is configured to direct the fluid towards the cavity,  
and wherein a channel is formed in the supporting member, the channel coupling the pump to  
the cavity such that the fluid flows through the channel to the cavity during use, and wherein  
the pump comprises a diaphragm pump, and wherein the pump comprises a piezoelectric  
pump.

62. The system of claim 1, wherein the sensor array further comprises a pump coupled to the  
supporting member, wherein the pump is configured to direct the fluid towards the cavity,  
and wherein a channel is formed in the supporting member, the channel coupling the pump to  
the cavity such that the fluid flows through the channel to the cavity during use, and wherein  
the pump comprises a diaphragm pump, and wherein the pump comprises a pneumatic  
activated pump.

63. The system of claim 1, wherein the sensor array further comprises a pump coupled to the  
supporting member, wherein the pump is configured to direct the fluid towards the cavity,  
and wherein a channel is formed in the supporting member, the channel coupling the pump to  
the cavity such that the fluid flows through the channel to the cavity during use, and wherein  
the pump comprises a diaphragm pump, and wherein the pump comprises a heat activated  
pump.

64. The system of claim 1, wherein the sensor array further comprises a pump coupled to the  
supporting member, wherein the pump is configured to direct the fluid towards the cavity,  
and wherein a channel is formed in the supporting member, the channel coupling the pump to  
the cavity such that the fluid flows through the channel to the cavity during use, and wherein  
the pump comprises a diaphragm pump, and wherein the pump comprises a peristaltic pump.

65. The system of claim 1, wherein the sensor array further comprises a pump coupled to the  
supporting member, wherein the pump is configured to direct the fluid towards the cavity,  
and wherein a channel is formed in the supporting member, the channel coupling the pump to

the cavity such that the fluid flows through the channel to the cavity during use, and wherein the pump comprises a diaphragm pump, and wherein the pump comprises an electroosmosis pump.

5 66. The system of claim 1, wherein the sensor array further comprises a pump coupled to the supporting member, wherein the pump is configured to direct the fluid towards the cavity, and wherein a channel is formed in the supporting member, the channel coupling the pump to the cavity such that the fluid flows through the channel to the cavity during use, and wherein the pump comprises a diaphragm pump, and wherein the pump comprises an  
10 electrohydrodynamic pump.

67. The system of claim 1, wherein the sensor array further comprises a pump coupled to the supporting member, wherein the pump is configured to direct the fluid towards the cavity, and wherein a channel is formed in the supporting member, the channel coupling the pump to the cavity such that the fluid flows through the channel to the cavity during use, and wherein the pump comprises a diaphragm pump, and wherein the pump comprises an electroosmosis pump and an electrohydrodynamic pump.  
5

68. The system of claim 1, wherein the particle comprises a receptor molecule coupled to a polymeric resin, and wherein the particle further comprises a first indicator and a second indicator, the first and second indicators being coupled to the receptor, wherein the interaction of the receptor with the analyte causes the first and second indicators to interact such that the signal is produced.  
10

25 69. The system of claim 1, wherein the particle comprises a receptor molecule coupled to a polymeric resin, and wherein the particle further comprises an indicator, wherein the indicator is associated with the receptor such that in the presence of the analyte the indicator is displaced from the receptor to produce the signal.

70. The system of claim 1, wherein a portion of the supporting member is substantially transparent to a portion of light produced by the light source.

71. The system of claim 1, wherein the particle is coupled to the supporting member with via an adhesive material.

72. The system of claim 1, wherein the particle are coupled to the supporting member via a gel material.

73. The system of claim 1, wherein the particle is suspended in a gel material, the gel material covering a portion of the supporting member, and wherein a portion of the particle extends from the upper surface of the gel.

74. The system of claim 1, wherein the sensor array further comprises a cover coupled to the supporting member, positioned above the particle, wherein a force exerted by the cover on the particle inhibits the displacement of the particle from the supporting member.

75. The system of claim 1, wherein the supporting member comprises glass.

76. The system of claim 1, wherein the supporting member is composed of a material substantially transparent to ultraviolet light.

77. The system of claim 1, further comprising a conduit coupled to the sensor array, wherein the conduit is configured to conduct the fluid sample to and away from the sensor array; and a vacuum chamber coupled to the conduit, wherein the vacuum chamber comprises a breakable barrier positioned between the chamber and the conduit, and wherein the chamber is configured to pull the fluid through the conduit when the breakable barrier is punctured.

78. The system of claim 1, further comprising a conduit coupled to the sensor array, wherein the

conduit is configured to conduct the fluid sample to and away from the sensor array; and a vacuum chamber coupled to the conduit, wherein the vacuum chamber comprises a breakable barrier positioned between the chamber and the conduit, and wherein the chamber is configured to pull the fluid through the conduit when the breakable barrier is punctured, and further comprising a filter coupled to the conduit and the sensor array, wherein the fluid passes through the filter before reaching the sensor array.

79. The system of claim 1, further comprising a conduit coupled to the sensor array, wherein the conduit is configured to conduct the fluid sample to and away from the sensor array; and a vacuum chamber coupled to the conduit, wherein the vacuum chamber comprises a breakable barrier positioned between the chamber and the conduit, and wherein the chamber is configured to pull the fluid through the conduit when the breakable barrier is punctured, and further comprising a filter coupled to the conduit and the sensor array, wherein the fluid passes through the filter before reaching the sensor array, and wherein the fluid is a blood sample, and wherein the filter comprises a membrane for the removal of particulates.

80. The system of claim 1, further comprising a conduit coupled to the sensor array, wherein the conduit is configured to conduct the fluid sample to and away from the sensor array; and a vacuum chamber coupled to the conduit, wherein the vacuum chamber comprises a breakable barrier positioned between the chamber and the conduit, and wherein the chamber is configured to pull the fluid through the conduit when the breakable barrier is punctured, and further comprising a filter coupled to the conduit and the sensor array, wherein the fluid passes through the filter before reaching the sensor array, and wherein the fluid is a blood sample, and wherein the filter comprises a membrane for removal of white and red blood cells from the blood.

81. The system of claim 1, wherein the particle comprises a biopolymer coupled to a polymeric resin, and wherein the biopolymer undergoes a chemical reaction in the presence of the analyte to produce a signal.

82. The system of claim 1, wherein the particle comprises a biopolymer coupled to a polymeric resin, and wherein the biopolymer undergoes a chemical reaction in the presence of the analyte to produce a signal, and wherein the chemical reaction comprises cleavage of the biopolymer by the analyte.

83. The system of claim 1, wherein the particle comprises a biopolymer coupled to a polymeric resin, and wherein the biopolymer undergoes a chemical reaction in the presence of the analyte to produce a signal, and wherein the biopolymer comprises a peptide, and wherein the analyte comprises a protease, and wherein the chemical reaction comprises cleavage of the peptide by the protease.

84. The system of claim 1, wherein the particle comprises a biopolymer coupled to a polymeric resin, and wherein the biopolymer undergoes a chemical reaction in the presence of the analyte to produce a signal, and wherein the biopolymer comprises a polynucleotide, and wherein the analyte comprises a nuclease, and wherein the chemical reaction comprises cleavage of the polynucleotide by the nuclease.

85. The system of claim 1, wherein the particle comprises a biopolymer coupled to a polymeric resin, and wherein the biopolymer undergoes a chemical reaction in the presence of the analyte to produce a signal, and wherein the biopolymer comprises an oligosaccharide, and wherein the analyte comprises an oligosaccharide cleaving agent, and wherein the chemical reaction comprises cleavage of the oligosaccharide by the oligosaccharide cleaving agent.

86. The system of claim 1, wherein the particle comprises a biopolymer coupled to a polymeric resin, and wherein the biopolymer undergoes a chemical reaction in the presence of the analyte to produce a signal, and wherein the particle further comprises a first indicator and a second indicator, the first and second indicators being coupled to the biopolymer, and wherein the chemical reaction of the biopolymer in the presence of the analyte causes a

distance between the first and second indicators to become altered such that the signal is produced.

87. The system of claim 1, wherein the particle comprises a biopolymer coupled to a polymeric resin, and wherein the biopolymer undergoes a chemical reaction in the presence of the analyte to produce a signal, and wherein the particle further comprises a first indicator and a second indicator, the first and second indicators being coupled to the biopolymer, and wherein the chemical reaction of the biopolymer in the presence of the analyte causes a distance between the first and second indicators to become altered such that the signal is produced, and wherein the first indicator is a fluorescent dye and wherein the second indicator is a fluorescent quencher, and wherein the first indicator and the second indicator are within the Föster energy transfer radius, and wherein the chemical reaction of the biopolymer in the presence of the analyte causes the first and second indicators to move outside the Föster energy transfer radius.

88. The system of claim 1, wherein the particle comprises a biopolymer coupled to a polymeric resin, and wherein the biopolymer undergoes a chemical reaction in the presence of the analyte to produce a signal, and wherein the particle further comprises a first indicator and a second indicator, the first and second indicators being coupled to the biopolymer, and wherein the chemical reaction of the biopolymer in the presence of the analyte causes a distance between the first and second indicators to become altered such that the signal is produced. wherein the first indicator is a fluorescent dye and wherein the second indicator is a different fluorescent dye, and wherein the first indicator and the second indicator produce a fluorescence resonance energy transfer signal, and wherein the chemical reaction of the biopolymer in the presence of the analyte causes the positions of the first and second indicators to change such that the fluorescence resonance energy transfer signal is altered.

89. The system of claim 1, wherein the particle comprises a biopolymer coupled to a polymeric resin, and wherein the biopolymer undergoes a chemical reaction in the presence of the

analyte to produce a signal, and further comprising an indicator coupled to the biopolymer, and wherein the chemical reaction of the biopolymer in the presence of the analyte causes the biopolymer to be cleaved such that a portion of the biopolymer coupled to the indicator is cleaved from a portion of the biopolymer coupled to the polymeric resin.

5

90. The system of claim 1 wherein the particle comprises a biopolymer coupled to a polymeric resin, and wherein the biopolymer undergoes a chemical reaction in the presence of the analyte to produce a signal, and wherein the particle further comprises an indicator coupled to the particle, and wherein the chemical reaction causes a change to a biopolymer such that the interaction of the indicator with the biopolymer is altered to produce the signal.

10

91. The system of claim 1, wherein the particle comprises a biopolymer coupled to a polymeric resin, and wherein the biopolymer undergoes a chemical reaction in the presence of the analyte to produce a signal, and wherein the particle further comprises an indicator coupled to the particle, and wherein the chemical reaction causes a change to the biopolymer and the indicator to produce the signal.

15

92. The system of claim 1, wherein the particle comprises a receptor coupled to a polymeric resin, and a probe molecule coupled to the polymeric resin, and wherein the probe molecule is configured to produce a signal when the receptor interacts with the analyte during use.

20

93. The system of claim 1, wherein the particle comprises a receptor coupled to a polymeric resin, and a probe molecule coupled to the polymeric resin, and wherein the probe molecule is configured to produce a signal when the receptor interacts with the analyte during use, and wherein the particles further comprises an additional probe molecule coupled to the polymeric resin, wherein the interaction of the receptor with the analyte causes the probe molecules to interact such that the signal is produced.

25

94. A system for detecting an analyte in a fluid comprising:

a light source;

a sensor array, the sensor array comprising:

a supporting member; wherein a first cavity and a second cavity are formed within the supporting member;

a first particle positioned within the first cavity;

a second particle positioned within the second cavity, wherein the second particle comprises a reagent, wherein a portion of the reagent is removable from the second particle when contacted with a decoupling solution, and wherein the reagent is configured to modify the first particle, when the reagent is contacted with the first particle, such that the first particle will produce a signal when the first particle interacts with the analyte during use;

a first pump coupled to the supporting member, wherein the pump is configured to direct the fluid towards the first cavity;

a second pump coupled to the supporting member, wherein the second pump is configured to direct the decoupling solution towards the second cavity;

wherein a first channel is formed in the supporting member, the first channel coupling the first pump to the first cavity such that the fluid flows through the first channel to the first cavity during use, and wherein a second channel is formed in the supporting member, the second channel coupling the second cavity to the first cavity such that the decoupling solution flows from the second cavity through the second channel to the first cavity during use; and



a detector, the detector being configured to detect the signal produced by the interaction of the analyte with the particle during use;

5 wherein the light source and detector are positioned such that light passes from the light source, to the particle, and onto the detector during use.

95. The system of claim 94, wherein the sensor array further comprises a plurality of additional particles positioned within a plurality of additional cavities, and wherein the system is  
10 configured to substantially simultaneously detect a plurality of analytes in the fluid, and wherein the second cavity is coupled to the additional cavities such that the reagent may be transferred from the second particle to the additional cavities during use.

96. The system of claim 94, wherein the first particle comprises an indicator molecule coupled to a first polymeric resin, and the second particle comprises a receptor molecule coupled to a  
15 second polymeric resin.

97. The system of claim 94, wherein the first particle comprises a first polymeric resin configured to bind to the receptor molecule, and wherein the second particle comprises the receptor molecule coupled to a second polymeric resin.  
20

98. The system of claim 94, wherein the sensor array further comprises a reservoir coupled to the second pump, the reservoir configured to hold the decoupling solution.

25 99. A system for detecting an analyte in a fluid comprising:

a light source;

a sensor array, the sensor array comprising at least one particle coupled to the sensor

array, wherein the particle is configured to produce a signal when the particle interacts with the analyte; and

a detector configured to detect the signal produced by the interaction of the analyte with the particle;

wherein the light source and detector are positioned such that light passes from the light source, to the particle, and onto the detector during use.

100. A sensor array for detecting an analyte in a fluid comprising:

a supporting member; wherein at least one cavity is formed within the supporting member;

a particle positioned within the cavity, wherein the particle is configured to produce a signal when the particle interacts with the analyte.

101. The sensor array of claim 100, further comprising a plurality of particles positioned within the cavity.

102. The sensor array of claim 100, wherein the particle comprises a receptor molecule coupled to a polymeric resin.

103. The sensor array of claim 100, wherein the particle has a size ranging from about 0.05 micron to about 500 microns in diameter.

104. The sensor array of claim 100, wherein the particle has a size ranging from about 0.05 micron to about 500 microns in diameter, and wherein the cavity is configured to substantially contain the particle.

Attorney's Office  
No. 5119-00529

- 105. The sensor array of claim 100, wherein the supporting member comprises a plastic material.
- 5 106. The sensor array of claim 100, wherein the supporting member comprises a silicon wafer.
- 107. The sensor array of claim 100, wherein the cavity extends through the supporting member.
- 10 108. The sensor array of claim 100, wherein the supporting member comprises a silicon wafer, and wherein the cavity is substantially pyramidal in shape and wherein the sidewalls of the cavity are substantially tapered at an angle of between about 50 to about 60 degrees.
- 109. The sensor array of claim 100, wherein the supporting member comprises a silicon wafer, and further comprising a substantially transparent layer positioned on a bottom surface of the silicon wafer.
- 110. The sensor array of claim 100, wherein the supporting member comprises a silicon wafer, and further comprising a substantially transparent layer positioned on a bottom surface of the silicon wafer, wherein the substantially transparent layer comprises silicon dioxide, silicon nitride, or silicon oxide/silicon nitride multilayer stacks.
- 111. The sensor array of claim 100, wherein the supporting member comprises a silicon wafer, and further comprising a substantially transparent layer positioned on a bottom surface of the silicon wafer, wherein the substantially transparent layer comprises silicon nitride.
- 25 112. The sensor array of claim 100, wherein the supporting member comprises a silicon wafer, and wherein the silicon wafer has an area of about 1 cm<sup>2</sup> to about 100 cm<sup>2</sup>.

113. The sensor array of claim 100, further comprising a plurality of cavities formed in the silicon wafer, and wherein from about 10 to about  $10^6$  cavities are formed in the silicon wafer.

5 114. The sensor array of claim 100, further comprising channels in the supporting member, wherein the channels are configured to allow the fluid to flow through the channels into and away from the cavity.

10 115. The sensor array of claim 100, further comprising an inner surface coating, wherein the inner surface coating is configured to inhibit dislodgment of the particle.

116. The sensor array of claim 100, further comprising a detector coupled to the bottom surface of the supporting member, wherein the detector is positioned below the cavity.

15 117. The sensor array of claim 100, further comprising a detector coupled to the bottom surface of the supporting member, wherein the detector is positioned below the cavity, and wherein the detector is a semiconductor based photodetector.

20 118. The sensor array of claim 100, further comprising a detector coupled to the bottom surface of the supporting member, wherein the detector is positioned below the cavity, and wherein the detector is a Fabry-Perot type detector.

25 119. The sensor array of claim 100, further comprising a detector coupled to the bottom surface of the supporting member, wherein the detector is positioned below the cavity, and further comprising an optical fiber coupled to the detector, wherein the optical fiber is configured to transmit optical data to a microprocessor.

120. The sensor array of claim 100, further comprising an optical filters coupled to a bottom surface of the sensor array.

121. The sensor array of claim 100, further comprising a barrier layer positioned over the cavity, the barrier layer being configured to inhibit dislodgment of the particle during use.

5 122. The sensor array of claim 100, further comprising a barrier layer positioned over the cavity, the barrier layer being configured to inhibit dislodgment of the particle during use, and wherein the barrier layer comprises a substantially transparent cover plate positioned over the cavity, and wherein the cover plate is positioned a fixed distance over the cavity such that the fluid can enter the cavity.

10

123. The sensor array of claim 100, further comprising a barrier layer positioned over the cavity, the barrier layer being configured to inhibit dislodgment of the particle during use, and wherein the barrier layer comprises a substantially transparent cover plate positioned over the cavity, and wherein the cover plate is positioned a fixed distance over the cavity such that the fluid can enter the cavity, and wherein the barrier layer comprises plastic, glass, quartz, silicon oxide, or silicon nitride.

15

124. The sensor array of claim 100, further comprising a plurality of particles positioned within a plurality of cavities formed in the supporting member.

20

125. The sensor array of claim 100, wherein the system comprises a plurality of particles positioned within a plurality of cavities, and wherein the plurality of particles produce a detectable pattern in the presence of the analyte.

25

126. The sensor array of claim 100, further comprising channels in the supporting member, wherein the channels are configured to allow the fluid to flow through the channels into and away from the cavities, and wherein the barrier layer comprises a cover plate positioned upon an upper surface of the supporting member, and wherein the cover plate inhibits passage of the fluid into the cavities such that the fluid enters the cavities via the channels.

127. The sensor array of claim 100, further comprising a cover layer coupled to the supporting member and a bottom layer coupled to the supporting member, wherein the bottom layer is coupled to a bottom surface of the supporting member and wherein the cover layer is removable, and wherein the cover layer and the bottom layer include openings that are substantially aligned with the cavities during use.

128. The sensor array of claim 100, further comprising a cover layer coupled to the supporting member and a bottom layer coupled to the supporting member, wherein an opening is formed in the cover layer substantially aligned with the cavity, and wherein an opening is formed in the bottom layer substantially aligned with the cavity.

129. The sensor array of claim 100, wherein the cavity is substantially tapered such that the width of the cavity narrows in a direction from a top surface of the supporting member toward a bottom surface of the supporting member, and wherein a minimum width of the cavity is substantially less than a width of the particle.

130. The sensor array of claim 100, wherein a width of a bottom portion of the cavity is substantially less than a width of a top portion of the cavity, and wherein the width of the bottom portion of the cavity is substantially less than a width of the particle.

131. The sensor array of claim 100, further comprising a cover layer coupled to the supporting member and a bottom layer coupled to the supporting member, wherein the bottom layer is configured to support the particle, and wherein an opening is formed in the cover layer substantially aligned with the cavity.

132. The sensor array of claim 100, further comprising a removable cover layer coupled to the supporting member.

133. The sensor array of claim 100, wherein the supporting member comprises a dry film photoresist material.

134. The sensor array of claim 100, wherein the supporting member comprises a plurality of layers of a dry film photoresist material.

135. The sensor array of claim 100, wherein an inner surface of the cavity is coated with a reflective material.

136. The sensor array of claim 100, further comprising channels in the supporting member, wherein the channels are configured to allow the fluid to flow through the channels into and away from the cavity.

137. The sensor array of claim 100, further comprising a pump coupled to the supporting member, wherein the pump is configured to direct the fluid towards the cavity; and a channel formed in the supporting member, the channel coupling the pump to the cavity such that the fluid flows through the channel to the cavity during use.

138. The sensor array of claim 100, further comprising a pump coupled to the supporting member, wherein the pump is configured to direct the fluid towards the cavity; and a channel formed in the supporting member, the channel coupling the pump to the cavity such that the fluid flows through the channel to the cavity during use, and wherein the pump comprises a diaphragm pump.

139. The sensor array of claim 100, further comprising a pump coupled to the supporting member, wherein the pump is configured to direct the fluid towards the cavity; and a channel formed in the supporting member, the channel coupling the pump to the cavity such that the fluid flows through the channel to the cavity during use, and wherein the pump comprises an electrode pump.

140. The sensor array of claim 100, further comprising a pump coupled to the supporting member, wherein the pump is configured to direct the fluid towards the cavity; and a channel formed in the supporting member, the channel coupling the pump to the cavity such that the fluid flows through the channel to the cavity during use, and wherein the pump comprises a piezoelectric pump.

141. The sensor array of claim 100, further comprising a pump coupled to the supporting member, wherein the pump is configured to direct the fluid towards the cavity; and a channel formed in the supporting member, the channel coupling the pump to the cavity such that the fluid flows through the channel to the cavity during use, and wherein the pump comprises a pneumatic activated pump.

142. The sensor array of claim 100, further comprising a pump coupled to the supporting member, wherein the pump is configured to direct the fluid towards the cavity; and a channel formed in the supporting member, the channel coupling the pump to the cavity such that the fluid flows through the channel to the cavity during use, and wherein the pump comprises a heat activated pump.

143. The sensor array of claim 100, further comprising a pump coupled to the supporting member, wherein the pump is configured to direct the fluid towards the cavity; and a channel formed in the supporting member, the channel coupling the pump to the cavity such that the fluid flows through the channel to the cavity during use, and wherein the pump comprises a peristaltic pump.

144. The sensor array of claim 100, further comprising a pump coupled to the supporting member, wherein the pump is configured to direct the fluid towards the cavity; and a channel formed in the supporting member, the channel coupling the pump to the cavity such that the



fluid flows through the channel to the cavity during use, and wherein the pump comprises an electroosmosis pump.

145. The sensor array of claim 100, further comprising a pump coupled to the supporting member, wherein the pump is configured to direct the fluid towards the cavity; and a channel formed in the supporting member, the channel coupling the pump to the cavity such that the fluid flows through the channel to the cavity during use, and wherein the pump comprises an electrohydrodynamic pump.

146. The sensor array of claim 100, further comprising a pump coupled to the supporting member, wherein the pump is configured to direct the fluid towards the cavity; and a channel formed in the supporting member, the channel coupling the pump to the cavity such that the fluid flows through the channel to the cavity during use, and wherein the pump comprises an electroosmosis pump and an electrohydrodynamic pump.

147. The sensor array of claim 100, wherein a width of a bottom portion of the cavity is substantially less than a width of a top portion of the cavity, and wherein the width of the bottom portion of the cavity is substantially less than a width of the particle.

148. A sensor array for detecting an analyte in a fluid comprising:

a supporting member; wherein a first cavity and a second cavity are formed within the supporting member;

a first particle positioned within the first cavity;

a second particle positioned within the second cavity, wherein the second particle comprises a reagent, wherein a portion of the reagent is removable from the second

particle when contacted with a decoupling solution, and wherein the reagent is configured to modify the first particle, when the reagent is contacted with the first particle, such that the first particle will produce a signal when the first particle interacts with the analyte during use;

a first pump coupled to the supporting member, wherein the pump is configured to direct the fluid towards the first cavity;

a second pump coupled to the supporting member, wherein the second pump is configured to direct the decoupling solution towards the second cavity;

wherein a first channel is formed in the supporting member, the first channel coupling the first pump to the first cavity such that the fluid flows through the first channel to the first cavity during use, and wherein a second channel is formed in the supporting member, the second channel coupling the second cavity to the first cavity such that the decoupling solution flows from the second cavity through the second channel to the first cavity during use.

149. The sensor array of claim 148, wherein the first particle comprises a receptor molecule coupled to a first polymeric resin, and wherein the second particle comprises an indicator molecule coupled to a second polymeric resin.

150. The sensor array of claim 148, wherein the first particle comprises an indicator molecule coupled to a first polymeric resin, and the second particle comprises a receptor molecule coupled to a second polymeric resin.

151. The sensor array of claim 148, wherein the first particle comprises a first polymeric resin configured to bind to the receptor molecule, and wherein the second particle comprises the receptor molecule coupled to a second polymeric resin.

152. The sensor array of claim 148, further comprising a reservoir coupled to the second pump, the reservoir configured to hold the decoupling solution.

5 153. A sensor array for detecting an analyte in a fluid comprising:

at least one particle coupled to a supporting member, wherein the particle is configured to produce a signal when the particle interacts with the analyte.

10 154. The sensor array of claim 153, wherein the particle is coupled to the supporting member with via an adhesive material.

155. The sensor array of claim 153, wherein the particle are coupled to the supporting member via a gel material.

156. The sensor array of claim 153, wherein the particle is suspended in a gel material, the gel material covering a portion of the supporting member, and wherein a portion of the particle extends from the upper surface of the gel.

157. The sensor array of claim 153, further comprising a cover positioned above the particle.

158. The sensor array of claim 153, further comprising a cover coupled to the supporting member, positioned above the particle, wherein a force exerted by the cover on the particle inhibits the displacement of the particle from the supporting member.

159. The sensor array of claim 153, wherein the particle comprises a receptor molecule coupled to a polymeric resin.

160. The sensor array of claim 153, wherein the supporting member comprises glass.

161. A method for forming a sensor array configured to detect an analyte in a fluid,  
comprising:

5 forming a cavity in a supporting member, wherein the supporting member comprises a  
silicon wafer;

placing a particle in the cavity, wherein the particle is configured to produce a signal  
when the particle interacts with the analyte; and

10 forming a cover upon a portion of the supporting member, wherein the cover is  
configured to inhibit dislodgment of the particle from the cavity.

162. The method of claim 161, wherein forming the cavity comprises anisotropically etching  
the silicon wafer.

163. The method of claim 161, wherein forming the cavity comprises anisotropically etching  
the silicon wafer with a wet hydroxide etch.

164. The method of claim 161, wherein forming the cavity comprises anisotropically etching  
the silicon wafer such that sidewalls of the cavity are tapered at an angle from about 50  
degrees to about 60 degrees.

165. The method of claim 161, wherein the silicon wafer has an area of about 1 cm<sup>2</sup> to about  
100 cm<sup>2</sup>.

166. The method of claim 161, further comprising forming a substantially transparent layer  
upon a bottom surface of the silicon wafer below the cavity.

167. The method of claim 161, further comprising forming a substantially transparent layer upon a bottom surface of the silicon wafer, wherein the cavity extends through the silicon wafer and wherein the substantially transparent layer is positioned to support the particle.

5 168. The method of claim 161, wherein the substantially transparent layer comprises silicon nitride.

169. The method of claim 161, wherein the cover comprises plastic, glass, quartz, silicon nitride, or silicon oxide.

10

170. The method of claim 161, wherein forming the cover comprises coupling the cover to the silicon wafer at a distance above the silicon wafer substantially less than a width of the particle.

15  
20  
25

171. The method of claim 161, further comprising etching channels in the silicon wafer prior to forming the cover on the silicon wafer, wherein forming the cover comprises placing the cover against the upper surface of the silicon wafer, and wherein the channels are configured to allow the fluid to pass through the silicon wafer to and from the cavities.

172. The method of claim 161, further comprising coating an inner surface of the cavity with a material to increase adhesion of the particle to the inner surface of the cavity.

173. The method of claim 161, further comprising coating an inner surface of the cavity with a material to increase reflectivity of the inner surface of the cavity.

25

174. The method of claim 161, further comprising forming an optical detector upon a bottom surface of the supporting member below the cavity.

175. The method of claim 161, further comprising forming a sensing cavity upon a bottom

surface of the supporting member below the cavity.

176. The method of claim 161, further comprising forming a sensing cavity upon a bottom surface of the supporting member below the cavity, and wherein forming the sensing cavity comprises:

forming a barrier layer upon a bottom surface of the silicon wafer;

forming a bottom diaphragm layer upon the barrier layer;

forming etch windows extending through the bottom diaphragm layer;

forming a sacrificial spacer layer upon the bottom diaphragm layer;

removing a portion of the spacer layer;

forming a top diaphragm layer; and

removing a remaining portion of the spacer layer.

177. The method of claim 161, further comprising forming an optical filter upon the bottom surface of the supporting member.

178. The method of claim 161, further comprising forming a plurality of cavities in the silicon wafer.

179. The method of claim 161, wherein from about  $10$  to about  $10^6$  cavities are formed in the silicon wafer.

180. The method of claim 161, wherein the formed cavity is configured to allow the fluid to pass through the supporting member.

181. The method of claim 161, further comprising forming a substantially transparent layer upon a bottom surface of the supporting member below the cavity, wherein the bottom layer is configured to inhibit the displacement of the particle from the cavity while allowing the fluid to pass through the supporting member.

182. The system of claim 161, wherein a width of a bottom portion of the cavity is substantially less than a width of a top portion of the cavity, and wherein the width of the bottom portion of the cavity is substantially less than a width of the particle.

183. The method of claim 161, further comprising forming channels in the supporting member wherein the channels are configured to allow the fluid to pass through the supporting member to and from the cavity.

184. The method of claim 161, further comprising forming a pump on the supporting member, the pump being configured to pump the fluid to the cavity.

185. The method of claim 161, further comprising forming a cover, wherein forming the cover comprises:

forming a removable layer upon the upper surface of the supporting member;

forming a cover upon the removable layer;

forming support structures upon the supporting member, the support structures covering a portion of the cover; and

dissolving the removable layer.

186. The method of claim 161, wherein forming the cover further comprises forming openings in the cover, wherein the openings are substantially aligned with the cavity.

5

187. The method of claim 161, wherein the particles are placed in the cavities using a micromanipulator.

188. The method of claim 161, further comprising forming additional cavities within the supporting member, and further comprising placing additional particles in the additional cavities, wherein placing the additional particles in the additional cavities comprises:

10

placing a first masking layer on the supporting member, wherein the first masking layer covers a first portion of the additional cavities such that passage of a particle into the first portion of the additional cavities is inhibited, and wherein the first masking layer a second portion of the cavities substantially unmasked,;

5

placing the additional particles on the supporting member;

moving the additional particles across the supporting member such that the particles fall into the second portion of the cavities;

20

removing the first masking layer;

placing a second masking layer upon the supporting member, wherein the second masking layer covers the second portion of the cavities and a portion of the first portion of the cavities while leaving a third portion of the cavities unmasked;

25

placing additional particles on the supporting member; and



moving the additional particles across the supporting member such that the particle fall into the third portion of the cavities.

5 189. The method of claim 161, wherein forming the cover comprises coupling the cover to the supporting member at a distance above the supporting member substantially less than a width of the particle.

10 190. The method of claim 161, wherein the supporting member comprises a dry film photoresist material.

191. The method of claim 161, wherein the supporting member comprises a plurality of layers of a dry film photoresist material.

5 192. The method of claim 161, wherein forming the cavity comprises:

etching a first opening through a first dry film photoresist layer, the first opening having a width substantially less than a width of the particle;

10 placing a second dry film photoresist layer upon the first dry film photoresist layer;

etching a second opening through the second dry film photoresist layer, the second opening being substantially aligned with the first opening, wherein a width of the second opening is substantially greater than the width of the first opening;

25 wherein the second dry film photoresist layer comprises a thickness substantially greater than a width of the particle;

and further comprising forming a reflective layer upon the inner surface of the cavity.

193. The method of claim 161, wherein the supporting material comprises a plastic material.

194. The method of claim 161, wherein the supporting material comprises a plastic material,  
5 and wherein the cavity is formed by drilling the supporting material.

195. The method of claim 161, wherein the supporting material comprises a plastic material,  
and wherein the cavity is formed by transfer molding the supporting member.

10 196. The method of claim 161, wherein the supporting material comprises a plastic material,  
and wherein the cavity is formed by a punching device.

197. A method of sensing an analyte in a fluid comprising:

15 passing a fluid over a sensor array, the sensor array comprising at least one particle  
positioned within a cavity of a supporting member;

20 monitoring a spectroscopic change of the particle as the fluid is passed over the sensor  
array, wherein the spectroscopic change is caused by the interaction of the analyte  
with the particle.

198. The method of claim 197, wherein the spectroscopic change comprises a change in  
absorbance of the particle.

25 199. The method of claim 197, wherein the spectroscopic change comprises a change in  
fluorescence of the particle.

200. The method of claim 197, wherein the spectroscopic change comprises a change in  
phosphorescence of the particle.

201. The method of claim 197, wherein the analyte is a proton atom, and wherein the spectroscopic change is produced when the pH of the fluid is varied, and wherein monitoring the spectroscopic change of the particle allows the pH of the fluid to be determined.

5

202. The method of claim 197, wherein the analyte is a metal cation, and wherein the spectroscopic change is produced in response to the presence of the metal cation in the fluid.

10

203. The method of claim 197, wherein the analyte is an anion, and wherein the spectroscopic change is produced in response to the presence of the anion in the fluid.

204. The method of claim 197, wherein the analyte is a DNA molecule, and wherein the spectroscopic change is produced in response to the presence of the DNA molecule in the fluid.

5

205. The method of claim 197, wherein the analyte is a protein, and wherein the spectroscopic change is produced in response to the presence of the protein in the fluid.

20

206. The method of claim 197, wherein the analyte is a metabolite, and wherein the spectroscopic change is produced in response to the presence of the metabolite in the fluid.

207. The method of claim 197, wherein the analyte is a sugar, and wherein the spectroscopic change is produced in response to the presence of the sugar in the fluid.

25

208. The method of claim 197, wherein the analyte is a bacteria, and wherein the spectroscopic change is produced in response to the presence of the bacteria in the fluid.

209. The method of claim 197, wherein the particle comprises a receptor coupled to a polymeric resin, and further comprising exposing the particle to an indicator prior to passing

the fluid over the sensor array.

210. The method of claim 197, wherein the particle comprises a receptor coupled to a polymeric resin, and further comprising exposing the particle to an indicator prior to passing  
5 the fluid over the sensor array, and wherein a binding strength of the indicator to the receptor is less than a binding strength of the analyte to the receptor.

211. The method of claim 197, wherein the particle comprises a receptor coupled to a polymeric resin, and further comprising exposing the particle to an indicator prior to passing  
10 the fluid over the sensor array, and wherein the indicator is a fluorescent indicator.

212. The method of claim 197, further comprising treating the fluid with an indicator prior to passing the fluid over the sensor array, wherein the indicator is configured to couple with the analyte.

213. The method of claim 197, wherein the analyte is bacteria and further comprising breaking down the bacteria prior to passing the fluid over the sensor array.

214. The method of claim 197, wherein monitoring the spectroscopic change is performed with a CCD device.

215. The method of claim 197, further comprising measuring the intensity of the spectroscopic change, and further comprising calculating the concentration of the analyte based on the intensity of the spectroscopic change.

216. The method of claim 197, wherein the supporting member comprises silicon.

217. The method of claim 197, wherein the spectroscopic change comprises a change in reflectance of the particle.

218. The method of claim 197, wherein the cavity is configured such that the fluid entering the cavity passes through the supporting member.

219. The method of claim 197, wherein monitoring the spectroscopic change comprises:

directing a red light source at the particle;

detecting the absorbance of red light by the particle;

directing a green light source at the particle;

detecting the absorbance of green light by the particle;

directing a blue light source at the particle; and

detecting the absorbance of blue light by the particle.

220. The method of claim 197, wherein the sensor array further comprises a vacuum chamber coupled to a conduit and the sensor array, and wherein the chamber is configured to provide a pulling force on the fluid in the sensor array.

221. The method of claim 197, wherein the fluid is blood.

222. The method of claim 197, further comprising passing the fluid through a filter prior to passing the fluid over the sensor array.

223. The method of claim 197, further comprising passing the fluid through a reagent reservoir prior to passing the fluid over the sensor array.

224. The method of claim 197, wherein the particles are initially stored in a buffer, and further comprising removing the buffer prior to passing the fluid over the sensor array.

225. The method of claim 197, wherein the particle comprises a polymeric resin, a biopolymer coupled to the polymeric resin, and wherein the biopolymer undergoes a chemical reaction in the presence of the analyte to produce a signal.

226. The method of claim 197, wherein the particle comprises a polymeric resin, a biopolymer coupled to the polymeric resin, and wherein the biopolymer undergoes a chemical reaction in the presence of the analyte to produce a signal, and wherein the signal comprises an absorbance of the particle.

227. The method of claim 197, wherein the particle comprises a polymeric resin, a biopolymer coupled to the polymeric resin, and wherein the biopolymer undergoes a chemical reaction in the presence of the analyte to produce a signal, and wherein the signal comprises a fluorescence of the particle.

228. The method of claim 197, wherein the particle comprises a polymeric resin, a biopolymer coupled to the polymeric resin, and wherein the biopolymer undergoes a chemical reaction in the presence of the analyte to produce a signal, and wherein the signal comprises a phosphorescence of the particle.

229. The method of claim 197, wherein the particle comprises a polymeric resin, a biopolymer coupled to the polymeric resin, and wherein the biopolymer undergoes a chemical reaction in the presence of the analyte to produce a signal, and wherein the chemical reaction comprises cleavage of the biopolymer induced by the analyte.

230. The method of claim 197, wherein the particle comprises a polymeric resin, a biopolymer

coupled to the polymeric resin, and wherein the biopolymer undergoes a chemical reaction in the presence of the analyte to produce a signal, and wherein the biopolymer comprises a peptide, and wherein the analyte comprises a protease, and wherein the chemical reaction comprises cleavage of the peptide by the protease.

5

231. The method of claim 197, wherein the particle comprises a polymeric resin, a biopolymer coupled to the polymeric resin, and wherein the biopolymer undergoes a chemical reaction in the presence of the analyte to produce a signal, and wherein the biopolymer comprises a polynucleotide, and wherein the analyte comprises a nuclease, and wherein the chemical reaction comprises cleavage of the polynucleotide by the nuclease.

10

232. The method of claim 197, wherein the particle comprises a polymeric resin, a biopolymer coupled to the polymeric resin, and wherein the biopolymer undergoes a chemical reaction in the presence of the analyte to produce a signal, and wherein the biopolymer comprises an oligosaccharide, and wherein the analyte comprises an oligosaccharide cleaving agent, and wherein the chemical reaction comprises cleavage of the oligosaccharide by the oligosaccharide cleaving agent.

5

233. The method of claim 197, wherein the particle comprises a polymeric resin, a biopolymer coupled to the polymeric resin, and wherein the biopolymer undergoes a chemical reaction in the presence of the analyte to produce a signal, and wherein the particle further comprises a first indicator and a second indicator, the first and second indicators being coupled to the biopolymer, and wherein the chemical reaction of the biopolymer in the presence of the analyte causes a distance between the first and second indicators to become altered such that the alteration of the signal is produced.

20

25

234. The method of claim 197, wherein the particle comprises a polymeric resin, a biopolymer coupled to the polymeric resin, and wherein the biopolymer undergoes a chemical reaction in the presence of the analyte to produce a signal, and wherein the particle further comprises a

first indicator and a second indicator, the first and second indicators being coupled to the biopolymer, and wherein the chemical reaction of the biopolymer in the presence of the analyte causes a distance between the first and second indicators to become altered such that the alteration of the signal is produced, and wherein the first indicator is a fluorescent dye and wherein the second indicator is a fluorescent quencher, and wherein the first indicator and the second indicator are within the Föster energy transfer radius, and wherein the chemical reaction of the biopolymer in the presence of the analyte causes the first and second indicators to move outside the Föster energy transfer radius such that the alteration of the signal is produced.

235. The method of claim 197, wherein the particle comprises a polymeric resin, a biopolymer coupled to the polymeric resin, and wherein the biopolymer undergoes a chemical reaction in the presence of the analyte to produce a signal, and wherein the particle further comprises a first indicator and a second indicator, the first and second indicators being coupled to the biopolymer, and wherein the chemical reaction of the biopolymer in the presence of the analyte causes a distance between the first and second indicators to become altered such that the alteration of the signal is produced, and wherein the first indicator is a fluorescent dye and wherein the second indicator is a different fluorescent dye, and wherein the first indicator and the second indicator produce a fluorescence resonance energy transfer signal, and wherein the chemical reaction of the biopolymer in the presence of the analyte causes the positions of the first and second indicators to change such that the fluorescence resonance energy transfer signal is altered producing the alteration in the signal.

236. The method of claim 197, wherein the particle comprises a polymeric resin, a biopolymer coupled to the polymeric resin, and wherein the biopolymer undergoes a chemical reaction in the presence of the analyte to produce a signal, and further comprising an indicator coupled to the biopolymer, and wherein the chemical reaction of the biopolymer in the presence of the analyte causes the biopolymer to be cleaved such that a portion of the biopolymer coupled to the indicator is cleaved from a portion of the biopolymer coupled to the polymeric resin.



237. The method of claim 197, wherein the particle comprises a receptor coupled to a polymeric resin, and a probe molecule coupled to the polymeric resin, and wherein the probe molecule is configured to produce a signal when the receptor interacts with the analyte during use.

238. The method of claim 197, wherein the particle comprises a receptor and an indicator coupled to a polymeric resin, wherein the indicator is configured to produce a signal when the receptor interacts with the analyte during use.

239. The method of claim 197, wherein the particle comprises a receptor and an indicator coupled to a polymeric resin, wherein the indicator is configured to produce a signal when the receptor interacts with the analyte during use, and wherein the receptor is coupled to the polymeric resin by a first linker and wherein the indicator is coupled to the polymeric resin by a second linker.

240. The method of claim 197, wherein the particle comprises a receptor and an indicator coupled to a polymeric resin, wherein the indicator is configured to produce a signal when the receptor interacts with the analyte during use, and wherein the receptor is coupled to the polymeric resin by a first linker and wherein the indicator is coupled to the polymeric resin by a second linker, and wherein the particle further comprises an additional indicator coupled to the polymeric resin by a third linker, wherein the interaction of the receptor with the analyte causes the indicator and the additional indicator to interact such that the signal is produced.

241. The method of claim 197, wherein the particle comprises a receptor and an indicator coupled to a polymeric resin, wherein the indicator is configured to produce a signal when the receptor interacts with the analyte during use, and wherein the receptor is coupled to the polymeric resin by a first linker and wherein the indicator is coupled to the receptor.

242. The method of claim 197, wherein the particle comprises a receptor and an indicator coupled to a polymeric resin, wherein the indicator is configured to produce a signal when the receptor interacts with the analyte during use, and wherein the receptor is coupled to the polymeric resin by a first linker and wherein the indicator is coupled to the receptor, and wherein the particle further comprises an additional indicator coupled to the receptor, wherein the interaction of the receptor with the analyte causes the indicator and the additional indicator to interact such that the signal is produced.

243. The method of claim 197, wherein the particle comprises a receptor and an indicator coupled to a polymeric resin, wherein the indicator is configured to produce a signal when the receptor interacts with the analyte during use, and wherein the receptor is coupled to the polymeric resin by a first linker and wherein the indicator is coupled to the receptor by a second linker.

244. The method of claim 197, wherein the particle comprises a receptor and an indicator coupled to a polymeric resin, wherein the indicator is configured to produce a signal when the receptor interacts with the analyte during use, and wherein the receptor is coupled to the polymeric resin by a first linker and wherein the indicator is coupled to the receptor by a second linker, and wherein the particle further comprises an additional indicator coupled to the receptor, wherein the interaction of the receptor with the analyte causes the indicator and the additional indicator to interact such that the signal is produced.

245. The method of claim 197, wherein the particle comprises a receptor and an indicator coupled to a polymeric resin, wherein the indicator is configured to produce a signal when the receptor interacts with the analyte during use, and wherein the receptor is coupled to the polymeric resin by a first linker and wherein the indicator is coupled to the first linker.

246. The method of claim 197, wherein the particle comprises a receptor and an indicator coupled to a polymeric resin, wherein the indicator is configured to produce a signal when the

receptor interacts with the analyte during use, and wherein the receptor is coupled to the polymeric resin by a first linker, and wherein the indicator is coupled to the first linker by a second linker.

247. The method of claim 197, wherein the particle comprises a receptor and an indicator coupled to a polymeric resin, wherein the indicator is configured to produce a signal when the receptor interacts with the analyte during use, and wherein the receptor is coupled to the polymeric resin by a first linker, and wherein the indicator is coupled to the first linker by a second linker, and wherein the particle further comprises an additional indicator coupled to the receptor, wherein the interaction of the receptor with the analyte causes the indicator and the additional indicator to interact such that the signal is produced.

248. The method of claim 197, wherein the particle comprises a receptor and an indicator coupled to a polymeric resin, wherein the indicator is configured to produce a signal when the receptor interacts with the analyte during use, and wherein the receptor is coupled to the polymeric resin by a first linker, and wherein the indicator is coupled to the first linker by a second linker, and wherein the particle further comprises an additional indicator coupled to the first linker by a third linker, wherein the interaction of the receptor with the analyte causes the indicator and the additional indicator to interact such that the signal is produced.

249. The method of claim 197, wherein the particle comprises a receptor and an indicator coupled to a polymeric resin, wherein the indicator is configured to produce a signal when the receptor interacts with the analyte during use, and wherein the indicator interacts with the receptor in the absence of an analyte.

250. The method of claim 197, wherein the particle comprises a receptor and an indicator coupled to a polymeric resin, wherein the indicator is configured to produce a signal when the receptor interacts with the analyte during use, and wherein the particle further comprises an additional indicator coupled to the polymeric resin, and wherein the indicator is a first

fluorescent dye and wherein the additional indicator is a second fluorescent dye, and wherein the indicator and the additional indicator produce a fluorescence resonance energy transfer signal, and wherein the interaction of the analyte with the receptor causes the distance between the indicator and the additional indicator to become altered such that the fluorescence resonance energy transfer signal is altered.

251. The method of claim 197, wherein the particle comprises a receptor and an indicator coupled to a polymeric resin, wherein the indicator is configured to produce a signal when the receptor interacts with the analyte during use, and wherein the particle further comprises an additional indicator coupled to the polymeric resin, wherein the indicator is a fluorescent dye and wherein the additional indicator is a fluorescence quencher, and wherein the indicator and the additional indicator are positioned such that the fluorescence of the indicator is at least partially quenched by the additional indicator, and wherein the interaction of the analyte with the receptor causes the distance between the indicator and the additional indicator to become altered such that the quenching of the fluorescence of the indicator by the additional indicator is altered.

252. The method of claim 197, wherein the particle comprises a biopolymer coupled to a polymeric resin, and wherein the biopolymer undergoes a chemical reaction in the presence of the analyte to produce a signal, and wherein the biopolymer undergoes a chemical reaction in the presence of the analyte such that the signal is altered.

253. A particle for detecting an analyte in a fluid comprising:

a polymeric resin;

a biopolymer coupled to the polymeric resin; and

an indicator system coupled to the biopolymer, the indicator system producing a

signal, and wherein the biopolymer undergoes a chemical reaction in the presence of the analyte such that the signal is altered.

254. The particle of claim 253, wherein the particle ranges from about 0.05 micron to about 500 microns.

255. The particle of claim 253, wherein a volume of the particle changes when contacted with the fluid.

256. The particle of claim 253, wherein the chemical reaction comprises cleavage of the biopolymer by the analyte.

257. The particle of claim 253, wherein the biopolymer comprises a peptide, and wherein the analyte comprises a protease, and wherein the chemical reaction comprises cleavage of the peptide by the protease.

258. The particle of claim 253, wherein the biopolymer comprises a polynucleotide, and wherein the analyte comprises a nuclease, and wherein the chemical reaction comprises cleavage of the polynucleotide by the nuclease.

259. The particle of claim 253, wherein the biopolymer comprises an oligosaccharide, and wherein the analyte comprises an oligosaccharide cleaving agent, and wherein the chemical reaction comprises cleavage of the oligosaccharide by the oligosaccharide cleaving agent.

260. The particle of claim 253, wherein the particle indicator system comprises a first indicator and a second indicator, and wherein the chemical reaction of the biopolymer in the presence of the analyte causes a distance between the first and second indicators to become altered such that the signal is produced.

261. The particle of claim 253, wherein the first indicator is a fluorescent dye and wherein the second indicator is a fluorescent quencher, and wherein the first indicator and the second indicator are within the Förster energy transfer radius, and wherein the chemical reaction of the biopolymer in the presence of the analyte causes the first and second indicators to move outside the Förster energy transfer radius.

262. The particle of claim 253, wherein the first indicator is a fluorescent dye and wherein the second indicator is a different fluorescent dye, and wherein the first indicator and the second indicator produce a fluorescence resonance energy transfer signal, and wherein the chemical reaction of the biopolymer in the presence of the analyte causes the positions of the first and second indicators to change such that the fluorescence resonance energy transfer signal is altered.

263. The particle of claim 253, wherein the indicator system comprises at least one indicator coupled to the biopolymer, and wherein the chemical reaction of the biopolymer in the presence of the analyte causes the biopolymer to be cleaved such that a portion of the biopolymer coupled to the indicator is cleaved from a portion of the biopolymer coupled to the polymeric resin.

264. A particle for detecting an analyte in a fluid comprising:

a polymeric resin;

a receptor coupled to the polymeric resin; and

a probe molecule coupled to the biopolymer, the probe molecule configured to produce a signal when the receptor interacts with the analyte during use.

265. The particle of claim 264, wherein the analyte comprises a metal ion, and wherein the

probe molecule produces the signal in response to the interaction of the metal ion with the receptor.

266. The particle of claim 264, wherein the particles further comprises an additional probe  
5 molecule coupled to the polymeric resin, wherein the interaction of the receptor with the analyte causes the probe molecules to interact such that the signal is produced.

267. The particle of claim 264, wherein the receptor comprises a polynucleotide.

10 268. The particle of claim 264, wherein the receptor comprises a peptide.

269. The particle of claim 264, wherein the receptor comprises an enzyme.

270. The particle of claim 264, wherein the receptor comprises a synthetic receptor.

271. The particle of claim 264, wherein the receptor comprises an unnatural biopolymer.

272. The particle of claim 264, wherein the receptor comprises an antibody.

20 273. The particle of claim 264, wherein the receptor comprises an antigen.

274. The particle of claim 264, wherein the analyte comprises phosphate functional groups,  
and wherein the particle is configured to produce the signal in the presence of the phosphate  
functional groups.

25 275. The particle of claim 264, wherein the analyte comprises bacteria, and wherein the particle is configured to produce the signal in the presence of the bacteria.

276. The particle of claim 264, wherein the receptor comprises an antibody, an aptamer, an

organic receptor, or an enzyme.

277. The particle of claim 264, wherein the probe molecule comprises an indicator, a dye, a quantum particle, or a semi-conductor particle.

5

278. A particle for detecting an analyte in a fluid comprising:

a polymeric resin;

10

a receptor coupled to the polymeric resin by a first linker; and

an indicator coupled to the first linker, the indicator configured to produce a signal when the receptor interacts with the analyte during use.

15  
20  
25  
30  
35  
40  
45  
50  
55  
60  
65  
70  
75  
80  
85  
90  
95  
100  
105  
110  
115  
120  
125  
130  
135  
140  
145  
150  
155  
160  
165  
170  
175  
180  
185  
190  
195  
200  
205  
210  
215  
220  
225  
230  
235  
240  
245  
250  
255  
260  
265  
270  
275  
280  
285  
290  
295  
300  
305  
310  
315  
320  
325  
330  
335  
340  
345  
350  
355  
360  
365  
370  
375  
380  
385  
390  
395  
400  
405  
410  
415  
420  
425  
430  
435  
440  
445  
450  
455  
460  
465  
470  
475  
480  
485  
490  
495  
500  
505  
510  
515  
520  
525  
530  
535  
540  
545  
550  
555  
560  
565  
570  
575  
580  
585  
590  
595  
600  
605  
610  
615  
620  
625  
630  
635  
640  
645  
650  
655  
660  
665  
670  
675  
680  
685  
690  
695  
700  
705  
710  
715  
720  
725  
730  
735  
740  
745  
750  
755  
760  
765  
770  
775  
780  
785  
790  
795  
800  
805  
810  
815  
820  
825  
830  
835  
840  
845  
850  
855  
860  
865  
870  
875  
880  
885  
890  
895  
900  
905  
910  
915  
920  
925  
930  
935  
940  
945  
950  
955  
960  
965  
970  
975  
980  
985  
990  
995


5

279. The particle of claim 278, wherein the receptor comprises a polynucleotide.

280. The particle of claim 278, wherein the receptor comprises a peptide.

281. The particle of claim 278, wherein the receptor comprises a compound of the general formula:

20



wherein X comprises carbocyclic systems or C<sub>1</sub>-C<sub>10</sub> alkanes, n is an integer of at least 1, m is an integer of at least 1; and

25

wherein each of R<sup>1</sup> independently represents -(CH<sub>2</sub>)<sub>y</sub>-NR<sup>3</sup>-C(NR<sup>4</sup>)-NR<sup>5</sup>, -(CH<sub>2</sub>)<sub>y</sub>-NR<sup>6</sup>R<sup>7</sup>, -(CH<sub>2</sub>)<sub>y</sub>-NH-Y, -(CH<sub>2</sub>)<sub>y</sub>-O-Z;

where y is an integer of at least 1;



where R<sup>3</sup>, R<sup>4</sup>, and R<sup>5</sup> independently represent hydrogen, alkyl, aryl, alkyl carbonyl of 1 to 10 carbon atoms, or alkoxy carbonyl of 1 to 10 carbon atoms, or R<sup>4</sup> and R<sup>5</sup> together represent a cycloalkyl group;

where R<sup>6</sup> represents hydrogen, alkyl, aryl, alkyl carbonyl of 1 to 10 carbon atoms, or alkoxy carbonyl of 1 to 10 carbon atoms;

where R<sup>7</sup> represents alkyl, aryl, alkyl carbonyl of 1 to 10 carbon atoms, or alkoxy carbonyl of 1 to 10 carbon atoms;

where R<sup>6</sup> and R<sup>7</sup> together represent a cycloalkyl group;

where Y is a peptide, or hydrogen

and where Z is a polynucleotide, an oligosaccharide or hydrogen; and

wherein each of R<sup>2</sup> independently represents hydrogen, alkyl, alkenyl, alkynyl, phenyl, phenylalkyl, arylalkyl, aryl, or together with another R<sup>2</sup> group represent a carbocyclic ring.

282. The particle of claim 278, wherein the receptor comprises an enzyme.

283. The particle of claim 278, wherein the receptor is coupled to the first linker by a second linker and wherein the indicator is coupled to the first linker by a third linker.

284. The particle of claim 278, wherein the receptor is coupled to the first linker by a second linker and wherein the indicator is coupled to the first linker by a third linker, and wherein the indicator interacts with the receptor in the absence of an analyte.

285. The particle of claim 278, wherein the particle further comprises an additional indicator coupled to the first linker, wherein the interaction of the receptor with the analyte causes the indicator and the additional indicator to interact such that the signal is produced.

286. The particle of claim 278, wherein the particle further comprises an additional indicator

coupled to the receptor, wherein the interaction of the receptor with the analyte causes the indicator and the additional indicator to interact such that the signal is produced.

287. The particle of claim 278, wherein the particle further comprises an additional indicator  
5 coupled to the first linker, and wherein the indicator is a first fluorescent dye and wherein the  
additional indicator is a second fluorescent dye, and wherein the indicator and the additional  
indicator produce a fluorescence resonance energy transfer signal, and wherein the interaction  
of the analyte with the receptor causes the distance between the indicator and the additional  
indicator to become altered such that the fluorescence resonance energy transfer signal is  
10 altered.

288. The particle of claim 278, wherein the particle further comprises an additional indicator  
coupled to the first linker, wherein the indicator is a fluorescent dye and wherein the  
additional indicator is a fluorescence quencher, and wherein the indicator and the additional  
indicator are positioned such that the fluorescence of the indicator is at least partially  
quenched by the additional indicator, and wherein the interaction of the analyte with the  
receptor causes the distance between the indicator and the additional indicator to become  
altered such that the quenching of the fluorescence of the indicator by the additional indicator  
is altered.

289. The particle of claim 278, wherein the particle further comprises an additional indicator  
coupled to the first linker, wherein the indicator is a fluorescence quencher and wherein the  
additional indicator is a fluorescent dye, and wherein the indicator and the additional  
indicator are positioned such that the fluorescence of the additional indicator is at least  
25 partially quenched by the indicator, and wherein the interaction of the analyte with the  
receptor causes the distance between the indicator and the additional indicator to become  
altered such that the quenching of the fluorescence of the additional indicator by the indicator  
is altered.

290. The particle of claim 278, wherein the particle further comprises an additional indicator coupled to the receptor, and wherein the indicator is a first fluorescent dye and wherein the additional indicator is a second fluorescent dye, and wherein the indicator and the additional indicator produce a fluorescence resonance energy transfer signal, and wherein the interaction of the analyte with the receptor causes the distance between the indicator and the additional indicator to become altered such that the fluorescence resonance energy transfer signal is altered.

291. The particle of claim 278, wherein the particle further comprises an additional indicator coupled to the receptor, wherein the indicator is a fluorescent dye and wherein the additional indicator is a fluorescence quencher, and wherein the indicator and the additional indicator are positioned such that the fluorescence of the indicator is at least partially quenched by the additional indicator, and wherein the interaction of the analyte with the receptor causes the distance between the indicator and the additional indicator to become altered such that the quenching of the fluorescence of the indicator by the additional indicator is altered.

292. The particle of claim 278, wherein the particle further comprises an additional indicator coupled to the receptor, wherein the indicator is a fluorescence quencher and wherein the additional indicator is a fluorescent dye, and wherein the indicator and the additional indicator are positioned such that the fluorescence of the additional indicator is at least partially quenched by the indicator, and wherein the interaction of the analyte with the receptor causes the distance between the indicator and the additional indicator to become altered such that the quenching of the fluorescence of the additional indicator by the indicator is altered.

293. The particle of claim 278, wherein the particle further comprises an additional indicator coupled to the first linker, wherein the receptor is coupled to the first linker by a second linker, the indicator is coupled to the first linker by a third linker and the additional indicator is coupled to the first linker by a fourth linker, and wherein the indicator is a first fluorescent

dye and wherein the additional indicator is a second fluorescent dye, and wherein the indicator and the additional indicator produce a fluorescence resonance energy transfer signal, and wherein the interaction of the analyte with the receptor causes the distance between the indicator and the additional indicator to become altered such that the fluorescence resonance energy transfer signal is altered.

294. The particle of claim 278, wherein the particle further comprises an additional indicator coupled to the first linker, wherein the receptor is coupled to the first linker by a second linker, the indicator is coupled to the first linker by a third linker and the additional indicator is coupled to the first linker by a fourth linker, wherein the indicator is a fluorescent dye and wherein the additional indicator is a fluorescence quencher, and wherein the indicator and the additional indicator are positioned such that the fluorescence of the indicator is at least partially quenched by the additional indicator, and wherein the interaction of the analyte with the receptor causes the distance between the indicator and the additional indicator to become altered such that the quenching of the fluorescence of the indicator by the additional indicator is altered.

295. The particle of claim 278, wherein the particle further comprises an additional indicator coupled to the first linker, wherein the receptor is coupled to the first linker by a second linker, the indicator is coupled to the first linker by a third linker and the additional indicator is coupled to the first linker by a fourth linker, wherein the indicator is a fluorescence quencher and wherein the additional indicator is a fluorescent dye, and wherein the indicator and the additional indicator are positioned such that the fluorescence of the additional indicator is at least partially quenched by the indicator, and wherein the interaction of the analyte with the receptor causes the distance between the indicator and the additional indicator to become altered such that the quenching of the fluorescence of the additional indicator by the indicator is altered.

296. The particle of claim 278, wherein the particle further comprises an additional indicator

coupled to the receptor, wherein the receptor is coupled to the first linker by a second linker, the indicator is coupled to the first linker by a third linker and the additional indicator is coupled to the receptor by a fourth linker, and wherein the indicator is a first fluorescent dye and wherein the additional indicator is a second fluorescent dye, and wherein the indicator and the additional indicator produce a fluorescence resonance energy transfer signal, and wherein the interaction of the analyte with the receptor causes the distance between the indicator and the additional indicator to become altered such that the fluorescence resonance energy transfer signal is altered.

297. The particle of claim 278, wherein the particle further comprises an additional indicator coupled to the receptor, wherein the receptor is coupled to the first linker by a second linker, the indicator is coupled to the first linker by a third linker and the additional indicator is coupled to the receptor by a fourth linker, wherein the indicator is a fluorescent dye and wherein the additional indicator is a fluorescence quencher, and wherein the indicator and the additional indicator are positioned such that the fluorescence of the indicator is at least partially quenched by the additional indicator, and wherein the interaction of the analyte with the receptor causes the distance between the indicator and the additional indicator to become altered such that the quenching of the fluorescence of the indicator by the additional indicator is altered.

298. The particle of claim 278, wherein the particle further comprises an additional indicator coupled to the receptor, wherein the receptor is coupled to the first linker by a second linker, the indicator is coupled to the first linker by a third linker and the additional indicator is coupled to the receptor by a fourth linker, wherein the indicator is a fluorescent dye and wherein the additional indicator is a fluorescence quencher, and wherein the indicator and the additional indicator are positioned such that the fluorescence of the indicator is at least partially quenched by the additional indicator, and wherein the interaction of the analyte with the receptor causes the distance between the indicator and the additional indicator to become altered such that the quenching of the fluorescence of the indicator by the additional indicator

is altered.

299. The particle of claim 278, wherein the particle further comprises an additional indicator coupled to the receptor, wherein the receptor is coupled to the first linker by a second linker, the indicator is coupled to the first linker by a third linker and the additional indicator is coupled to the receptor by a fourth linker, wherein the indicator is a fluorescence quencher and wherein the additional indicator is a fluorescent dye, and wherein the indicator and the additional indicator are positioned such that the fluorescence of the additional indicator is at least partially quenched by the indicator, and wherein the interaction of the analyte with the receptor causes the distance between the indicator and the additional indicator to become altered such that the quenching of the fluorescence of the additional indicator by the indicator is altered.

300. The particle of claim 278, wherein the polymeric resin comprises polystyrene-polyethylene glycol-divinyl benzene.

301. A particle for detecting an analyte in a fluid comprising:

a polymeric resin;

a biopolymer coupled to the polymeric resin; and

an indicator system coupled to the biopolymer, the indicator system producing a signal during use, and wherein the biopolymer undergoes a chemical reaction in the presence of the analyte such that the signal is altered during use.

302. The particle of claim 301, wherein the chemical reaction comprises cleavage of at least a portion of the biopolymer by the analyte.

303. The particle of claim 301, wherein the biopolymer comprises a polynucleotide, and wherein the analyte comprises a nuclease, and wherein the chemical reaction comprises cleavage of at least a portion of the polynucleotide by the nuclease.

5 304. The particle of claim 301, wherein the biopolymer comprises an oligosaccharide, and wherein the analyte comprises an oligosaccharide cleaving agent, and wherein the chemical reaction comprises cleavage of at least a portion of the oligosaccharide by the oligosaccharide cleaving agent.

10 305. The particle of claim 301, wherein the particle indicator system comprises a first indicator and a second indicator, and wherein the chemical reaction of the biopolymer in the presence of the analyte causes a distance between the first and second indicators to become altered such that the signal is produced.

15 306. The particle of claim 689, wherein the first indicator is a fluorescent dye and wherein the second indicator is a fluorescence quencher, and wherein the first indicator and the second indicator are positioned such that the fluorescence of the first indicator is at least partially quenched by the second indicator, and wherein the chemical reaction of the biopolymer in the presence of the analyte causes the first and second indicators to move such that the quenching  
20 of the fluorescence of the first indicator by the second indicator is altered.

307. The particle of claim 689, wherein the first indicator is a fluorescent dye and wherein the second indicator is a different fluorescent dye, and wherein the first indicator and the second indicator produce a fluorescence resonance energy transfer signal, and wherein the chemical  
25 reaction of the biopolymer in the presence of the analyte causes the positions of the first and second indicators to change such that the fluorescence resonance energy transfer signal is altered.

308. The particle of claim 301, wherein the indicator system comprises at least one indicator

coupled to the biopolymer, and wherein the chemical reaction of the biopolymer in the presence of the analyte causes the biopolymer to be cleaved such that at least a portion of the biopolymer coupled to the indicator is cleaved from at least a portion of the biopolymer coupled to the polymeric resin.

5

309. A system for detecting an analyte in a fluid comprising:

a body, wherein a sensor array system is positioned within the body, the sensor array system comprising

10

a light source;

a sensor array, the sensor array comprising a supporting member comprising at least one cavity formed within the supporting member;

a particle, the particle positioned within the cavity, wherein the particle is configured to produce a signal when the particle interacts with the analyte during use; and

a detector, the detector being configured to detect the signal produced by the interaction of the analyte with the particle during use;

wherein the light source and detector are positioned such that light passes from the light source, to the particle, and onto the detector during use.

25 310. The system of claim 309, wherein the sensor array is positioned within a cartridge, and wherein the cartridge is removable from the body.

311. The system of claim 309, further comprising a sample input port, positioned on the body, wherein the sample input port is coupled to the sensor array such that samples introduced into the



input port are transferred to the sensor array.

312. The system of claim 309, further comprising a sample input port, positioned on the body,  
wherein the sample input port is coupled to the sensor array such that samples introduced into the  
input port are transferred to the sensor array, and wherein the sample input port is configured to  
receive a syringe.

313. The system of claim 309, further comprising a sample input port and a filter, wherein the  
sample input is positioned on the body, and wherein the sample input port is coupled to the  
sensor array such that samples introduced into the input port are transferred to the sensor array,  
and wherein the filter is coupled to the sample input port.

314. The system of claim 309, further comprising a fluid cartridge coupled to the body and the  
sensor array.

315. The system of claim 309, further comprising an electronic controller coupled to the  
sensor array, the light source and the detector, wherein the electronic controller controls the  
operation of the sensor array system.

316. The system of claim 309, further comprising a global positioning system coupled to the  
body.

317. The system of claim 309, further comprising a data transfer system.

318. The system of claim 309, wherein the detector comprises a monochrome detector.

319. The system of claim 309, wherein the detector comprises a color detector.

320. The system of claim 309, wherein the light source comprises at least one light-emitting

diode.

321. The system of claim 309, wherein the light source comprises a light emitting diode.

5 322. The system of claim 309, wherein the system has a weight that allows the system to be carried by an operator.

323. The system of claim 309, further comprising a fluid delivery system coupled to the supporting member.

10

324. The system of claim 309, wherein the detector comprises a charge-coupled device.

325. The system of claim 309, wherein the particle comprises a receptor molecule coupled to a polymeric resin.

326. The system of claim 309, wherein the system comprises a plurality of particles positioned within a plurality of cavities, and wherein the system is configured to substantially simultaneously detect a plurality of analytes in the fluid.

20 327. The system of claim 309, wherein the particle ranges from about 0.05 micron to about 500 microns.

328. The system of claim 309, wherein a volume of the particle changes when contacted with the fluid.

25

329. The system of claim 309, wherein the particle further comprises a first indicator and a second indicator, the first and second indicators being coupled to the receptor, wherein the interaction of the receptor with the analyte causes the first and second indicators to interact such that the signal is produced.

330. The system of claim 309, wherein the particles further comprises an indicator, wherein the indicator is associated with the receptor such that in the presence of the analyte the indicator is displaced from the receptor to produce the signal.

5

331. The system of claim 309, wherein the supporting member comprises silicon.

332. The system of claim 309, wherein the supporting member further comprises channels in the supporting member, wherein the channels are configured to allow the fluid to flow through the channels into and away from the cavity.

10

333. The system of claim 309, wherein the supporting member further comprises a barrier layer positioned over the cavity, the barrier layer being configured to inhibit dislodgment of the particle during use.

334. The system of claim 309, wherein the supporting member further comprises a barrier layer positioned over the cavity, the barrier layer being configured to inhibit dislodgment of the particle during use, wherein the barrier layer comprises a substantially transparent cover plate positioned over the cavity, and wherein the cover plate is positioned a fixed distance over the cavity such that the fluid can enter the cavity.

20

335. The system of claim 309, wherein the supporting member comprises a plastic material.

336. The system of claim 309, wherein the supporting member comprises a dry film photoresist material.

25

337. The system of claim 309, wherein the cavity is configured such that the fluid entering the cavity passes through the supporting member during use.

338. The system of claim 309, further comprising a pump coupled to the supporting member, wherein the pump is configured to direct the fluid towards the cavity.

339. The system of claim 309, wherein a channel is formed in the supporting member, the  
5 channel coupling the pump to the cavity such that the fluid flows through the channel to the cavity during use.

340. The system of claim 309, further comprising a vacuum apparatus coupled to the sensor array, wherein the vacuum apparatus is configured to pull the fluid through the cavity during use.

10

11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100  
101  
102  
103  
104  
105  
106  
107  
108  
109  
110  
111  
112  
113  
114  
115  
116  
117  
118  
119  
120  
121  
122  
123  
124  
125  
126  
127  
128  
129  
130  
131  
132  
133  
134  
135  
136  
137  
138  
139  
140  
141  
142  
143  
144  
145  
146  
147  
148  
149  
150  
151  
152  
153  
154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178  
179  
180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200  
201  
202  
203  
204  
205  
206  
207  
208  
209  
210  
211  
212  
213  
214  
215  
216  
217  
218  
219  
220  
221  
222  
223  
224  
225  
226  
227  
228  
229  
230  
231  
232  
233  
234  
235  
236  
237  
238  
239  
240  
241  
242  
243  
244  
245  
246  
247  
248  
249  
250  
251  
252  
253  
254  
255  
256  
257  
258  
259  
260  
261  
262  
263  
264  
265  
266  
267  
268  
269  
270  
271  
272  
273  
274  
275  
276  
277  
278  
279  
280  
281  
282  
283  
284  
285  
286  
287  
288  
289  
290  
291  
292  
293  
294  
295  
296  
297  
298  
299  
300  
301  
302  
303  
304  
305  
306  
307  
308  
309  
310  
311  
312  
313  
314  
315  
316  
317  
318  
319  
320  
321  
322  
323  
324  
325  
326  
327  
328  
329  
330  
331  
332  
333  
334  
335  
336  
337  
338  
339  
340  
341  
342  
343  
344  
345  
346  
347  
348  
349  
350  
351  
352  
353  
354  
355  
356  
357  
358  
359  
360  
361  
362  
363  
364  
365  
366  
367  
368  
369  
370  
371  
372  
373  
374  
375  
376  
377  
378  
379  
380  
381  
382  
383  
384  
385  
386  
387  
388  
389  
390  
391  
392  
393  
394  
395  
396  
397  
398  
399  
400  
401  
402  
403  
404  
405  
406  
407  
408  
409  
410  
411  
412  
413  
414  
415  
416  
417  
418  
419  
420  
421  
422  
423  
424  
425  
426  
427  
428  
429  
430  
431  
432  
433  
434  
435  
436  
437  
438  
439  
440  
441  
442  
443  
444  
445  
446  
447  
448  
449  
450  
451  
452  
453  
454  
455  
456  
457  
458  
459  
460  
461  
462  
463  
464  
465  
466  
467  
468  
469  
470  
471  
472  
473  
474  
475  
476  
477  
478  
479  
480  
481  
482  
483  
484  
485  
486  
487  
488  
489  
490  
491  
492  
493  
494  
495  
496  
497  
498  
499  
500  
501  
502  
503  
504  
505  
506  
507  
508  
509  
510  
511  
512  
513  
514  
515  
516  
517  
518  
519  
520  
521  
522  
523  
524  
525  
526  
527  
528  
529  
530  
531  
532  
533  
534  
535  
536  
537  
538  
539  
540  
541  
542  
543  
544  
545  
546  
547  
548  
549  
550  
551  
552  
553  
554  
555  
556  
557  
558  
559  
560  
561  
562  
563  
564  
565  
566  
567  
568  
569  
570  
571  
572  
573  
574  
575  
576  
577  
578  
579  
580  
581  
582  
583  
584  
585  
586  
587  
588  
589  
590  
591  
592  
593  
594  
595  
596  
597  
598  
599  
600  
601  
602  
603  
604  
605  
606  
607  
608  
609  
610  
611  
612  
613  
614  
615  
616  
617  
618  
619  
620  
621  
622  
623  
624  
625  
626  
627  
628  
629  
630  
631  
632  
633  
634  
635  
636  
637  
638  
639  
640  
641  
642  
643  
644  
645  
646  
647  
648  
649  
650  
651  
652  
653  
654  
655  
656  
657  
658  
659  
660  
661  
662  
663  
664  
665  
666  
667  
668  
669  
670  
671  
672  
673  
674  
675  
676  
677  
678  
679  
680  
681  
682  
683  
684  
685  
686  
687  
688  
689  
690  
691  
692  
693  
694  
695  
696  
697  
698  
699  
700  
701  
702  
703  
704  
705  
706  
707  
708  
709  
710  
711  
712  
713  
714  
715  
716  
717  
718  
719  
720  
721  
722  
723  
724  
725  
726  
727  
728  
729  
730  
731  
732  
733  
734  
735  
736  
737  
738  
739  
740  
741  
742  
743  
744  
745  
746  
747  
748  
749  
750  
751  
752  
753  
754  
755  
756  
757  
758  
759  
760  
761  
762  
763  
764  
765  
766  
767  
768  
769  
770  
771  
772  
773  
774  
775  
776  
777  
778  
779  
780  
781  
782  
783  
784  
785  
786  
787  
788  
789  
790  
791  
792  
793  
794  
795  
796  
797  
798  
799  
800  
801  
802  
803  
804  
805  
806  
807  
808  
809  
810  
811  
812  
813  
814  
815  
816  
817  
818  
819  
820  
821  
822  
823  
824  
825  
826  
827  
828  
829  
830  
831  
832  
833  
834  
835  
836  
837  
838  
839  
840  
841  
842  
843  
844  
845  
846  
847  
848  
849  
850  
851  
852  
853  
854  
855  
856  
857  
858  
859  
860  
861  
862  
863  
864  
865  
866  
867  
868  
869  
870  
871  
872  
873  
874  
875  
876  
877  
878  
879  
880  
881  
882  
883  
884  
885  
886  
887  
888  
889  
890  
891  
892  
893  
894  
895  
896  
897  
898  
899  
900  
901  
902  
903  
904  
905  
906  
907  
908  
909  
910  
911  
912  
913  
914  
915  
916  
917  
918  
919  
920  
921  
922  
923  
924  
925  
926  
927  
928  
929  
930  
931  
932  
933  
934  
935  
936  
937  
938  
939  
940  
941  
942  
943  
944  
945  
946  
947  
948  
949  
950  
951  
952  
953  
954  
955  
956  
957  
958  
959  
960  
961  
962  
963  
964  
965  
966  
967  
968  
969  
970  
971  
972  
973  
974  
975  
976  
977  
978  
979  
980  
981  
982  
983  
984  
985  
986  
987  
988  
989  
990  
991  
992  
993  
994  
995  
996  
997  
998  
999  
1000  
1001  
1002  
1003  
1004  
1005  
1006  
1007  
1008  
1009  
1010  
1011  
1012  
1013  
1014  
1015  
1016  
1017  
1018  
1019  
1020  
1021  
1022  
1023  
1024  
1025  
1026  
1027  
1028  
1029  
1030  
1031  
1032  
1033  
1034  
1035  
1036  
1037  
1038  
1039  
1040  
1041  
1042  
1043  
1044  
1045  
1046  
1047  
1048  
1049  
1050  
1051  
1052  
1053  
1054  
1055  
1056  
1057  
1058  
1059  
1060  
1061  
1062  
1063  
1064  
1065  
1066  
1067  
1068  
1069  
1070  
1071  
1072  
1073  
1074  
1075  
1076  
1077  
1078  
1079  
1080  
1081  
1082  
1083  
1084  
1085  
1086  
1087  
1088  
1089  
1090  
1091  
1092  
1093  
1094  
1095  
1096  
1097  
1098  
1099  
1100  
1101  
1102  
1103  
1104  
1105  
1106  
1107  
1108  
1109  
1110  
1111  
1112  
1113  
1114  
1115  
1116  
1117  
1118  
1119  
1120  
1121  
1122  
1123  
1124  
1125  
1126  
1127  
1128  
1129  
1130  
1131  
1132  
1133  
1134  
1135  
1136  
1137  
1138  
1139  
1140  
1141  
1142  
1143  
1144  
1145  
1146  
1147  
1148  
1149  
1150  
1151  
1152  
1153  
1154  
1155  
1156  
1157  
1158  
1159  
1160  
1161  
1162  
1163  
1164  
1165  
1166  
1167  
1168  
1169  
1170  
1171  
1172  
1173  
1174  
1175  
1176  
1177  
1178  
1179  
1180  
1181  
1182  
1183  
1184  
1185  
1186  
1187  
1188  
1189  
1190  
1191  
1192  
1193  
1194  
1195  
1196  
1197  
1198  
1199  
1200  
1201  
1202  
1203  
1204  
1205  
1206  
1207  
1208  
1209  
1210  
1211  
1212  
1213  
1214  
1215  
1216  
1217  
1218  
1219  
1220  
1221  
1222  
1223  
1224  
1225  
1226  
1227  
1228  
1229  
1230  
1231  
1232  
1233  
1234  
1235  
1236  
1237  
1238  
1239  
1240  
1241  
1242  
1243  
1244  
1245  
1246  
1247  
1248  
1249  
1250  
1251  
1252  
1253  
1254  
1255  
1256  
1257  
1258  
1259  
1260  
1261  
1262  
1263  
1264  
1265  
1266  
1267  
1268  
1269  
1270  
1271  
1272  
1273  
1274  
1275  
1276  
1277  
1278  
1279  
1280  
1281  
1282  
1283  
1284  
1285  
1286  
1287  
1288  
1289  
1290  
1291  
1292  
1293  
1294  
1295  
1296  
1297  
1298  
1299  
1300  
1301  
1302  
1303  
1304  
1305  
1306  
1307  
1308  
1309  
1310  
1311  
1312  
1313  
1314  
1315  
1316  
1317  
1318  
1319  
1320  
1321  
1322  
1323  
1324  
1325  
1326  
1327  
1328  
1329  
1330  
1331  
1332  
1333  
1334  
1335  
1336  
1337  
1338  
1339  
1340  
1341  
1342  
1343  
1344  
1345  
1346  
1347  
1348  
1349  
1350  
1351  
1352  
1353  
1354  
1355  
1356  
1357  
1358  
1359  
1360  
1361  
1362  
1363  
1364  
1365  
1366  
1367  
1368  
1369  
1370  
1371  
1372  
1373  
1374  
1375  
1376  
1377  
1378  
1379  
1380  
1381  
1382  
1383  
1384  
1385  
1386  
1387  
1388  
1389  
1390  
1391  
1392  
1393  
1394  
1395  
1396  
1397  
1398  
1399  
1400  
1401  
1402  
1403  
1404  
1405  
1406  
1407  
1408  
1409  
1410  
1411  
1412  
1413  
1414  
1415  
1416  
1417  
1418  
1419  
1420  
1421  
1422  
1423  
1424  
1425  
1426  
1427  
1428  
1429  
1430  
1431  
1432  
1433  
1434  
1435  
1436  
1437  
1438  
1439  
1440  
1441  
1442  
1443  
1444  
1445  
1446  
1447  
1448  
1449  
1450  
1451  
1452  
1453  
1454  
1455  
1456  
1457  
1458  
1459  
1460  
1461  
1462  
1463  
1464  
1465  
1466  
1467  
1468  
1469  
1470  
1471  
1472  
1473  
1474  
1475  
1476  
1477  
1478  
1479  
1480  
1481  
1482  
1483  
1484  
1485  
1486  
1487  
1488  
1489  
1490  
1491  
1492  
1493  
1494  
1495  
1496  
1497  
1498  
1499  
1500  
1501  
1502  
1503  
1504  
1505  
1506  
1507  
1508  
1509  
1510  
1511  
1512  
1513  
1514  
1515  
1516  
1517  
1518  
1519  
1520  
1521  
1522  
1523  
1524  
1525  
1526  
1527  
1528  
1529  
1530  
1531  
1532  
1533  
1534  
1535  
1536  
1537  
1538  
1539  
1540  
1541  
1542  
1543  
1544  
1545  
1546  
1547  
1548  
1549  
1550  
1551  
1552  
1553  
1554  
1555  
1556  
1557  
1558  
1559  
1560  
1561  
1562  
1563  
1564  
1565  
1566  
1567  
1568  
1569  
1570  
1571  
1572  
1573  
1574  
1575  
1576  
1577  
1578  
1579  
1580  
1581  
1582  
1583  
1584  
1585  
1586  
1587  
1588  
1589  
1590  
1591  
1592  
1593  
1594  
1595  
1596  
1597  
1598  
1599  
1600  
1601  
1602  
1603  
1604  
1605  
1606  
1607  
1608  
1609  
1610  
1611  
1612  
1613  
1614  
1615  
1616  
1617  
1618  
1619  
1620  
1621  
1622  
1623  
1624  
1625  
1626  
1627  
1628  
1629  
1630  
1631  
1632  
1633  
1634  
1635  
1636  
1637  
1638  
1639  
1640  
1641  
1642  
1643  
1644  
1645  
1646  
1647  
1648  
1649  
1650  
1651  
1652  
1653  
1654  
1655  
1656  
1657  
1658  
1659  
1660  
1661  
1662  
1663  
1664  
1665  
1666  
1667  
1668  
1669  
1670  
1671  
1672  
1673  
1674  
1675  
1676  
1677  
1678  
1679  
1680  
1681  
1682  
1683  
1684  
1685  
1686  
1687  
1688  
1689  
1690  
1691  
1692  
1693  
1694  
1695  
1696  
1697  
1698  
1699  
1700  
1701  
1702  
1703  
1704  
1705  
1706  
1707  
1708  
1709  
1710  
1711  
1712  
1713  
1714  
1715  
1716  
1717  
1718  
1719  
1720  
1721  
1722  
1723  
1724  
1725  
1726  
1727  
1728  
1729  
1730  
1731  
1732  
1733  
1734  
1735  
1736  
1737  
1738  
1739  
1740  
1741  
1742  
1743  
1744  
1745  
1746  
1747  
1748  
1749  
1750  
1751  
1752  
1753  
1754  
1755  
1756  
1757  
1758  
1759  
1760  
1761  
1762  
1763  
1764  
1765  
1766  
1767  
1768  
1769  
1770  
1771  
1772  
1773  
1774  
1775  
1776  
1777  
1778  
1779  
1780  
1781  
1782  
1783  
1784  
1785  
1786  
1787  
1788  
1789  
1790  
1791  
1792  
1793  
1794  
1795  
1796  
1797  
1798  
1799  
1800  
1801  
1802  
1803  
1804  
1805  
1806  
1807  
1808  
1809  
1810  
1811  
1812  
1813  
1814  
1815  
1816  
1817  
1818  
1819  
1820  
1821  
1822  
1823  
1824  
1825  
1826  
1827  
1828  
1829  
1830  
1831  
1832  
1833  
1834  
1835  
1836  
1837  
1838  
1839  
1840  
1841  
1842  
1843  
1844  
1845  
1846  
1847  
1848  
1849  
1850  
1851  
1852  
1853  
1854  
1855  
1856  
1857  
1858  
1859  
1860  
1861  
1862  
1863  
1864  
1865  
1866  
1867  
1868  
1869  
1870  
1871  
1872  
1873  
1874  
1875  
1876  
1877  
1878  
1879  
1880  
1881  
1882  
1883  
1884  
1885  
1886  
1887  
1888  
1889  
1890  
1891  
1892  
1893  
1894  
1895  
1896  
1897  
1898  
1899  
1900  
1901  
1902  
1903  
1904  
1905  
1906  
1907  
1908  
1909  
1910  
1911  
1912  
1913  
1914  
1915  
1916  
1917  
1918  
1919  
1920  
1921  
1922  
1923  
1924  
1925  
1926  
1927  
1928  
1929  
1930  
1931  
1932  
1933  
1934  
1935  
1936  
1937  
1938  
1939  
1940  
1941  
1942  
1943  
1944  
1945  
1946  
1947  
1948  
1949  
1950  
1951  
1952  
1953  
1954  
1955  
1956  
1957  
1958  
1959  
1960  
1961  
1962  
1963  
1964  
1965  
1966  
1967  
1968  
1969  
1970  
1971  
1972  
1973  
1974  
1975  
1976  
1977  
1978  
1979  
1980  
1981  
1982  
1983  
1984  
1985  
1986  
1987  
1988  
1989  
1990  
1991  
1992  
1993  
1994  
1995  
1996  
1997  
1998  
1999  
2000  
2001  
2002  
2003  
2004  
2005  
2006  
2007  
2008  
2009  
2010  
2011  
2012  
2013  
2014  
2015  
2016  
2017  
2018  
2019  
2020  
2021  
2022  
2023  
2024  
2025  
2026  
2027  
2028  
2029  
2030  
2031  
2032  
2033  
2034  
2035  
2036  
2037  
2038  
2039  
2040  
2041  
2042  
2043  
2044  
2045  
2046  
2047  
2048  
2049  
2050  
2051  
2052  
2053  
2054  
2055  
2056  
2057  
2058  
2059  
2060  
2061  
2062  
2063  
2064  
2065  
2066  
2067  
2068  
2069  
2070  
2071  
2072  
2073  
2074  
2075  
2076  
2077  
2078  
2079  
2080  
2081  
2082  
2083  
2084  
2085  
2086  
2087  
2088  
2089  
2090  
2091  
2092  
2093  
2094  
2095  
2096  
2097  
2098  
2099  
2100  
2101  
2102  
2103  
2104  
2105  
2106  
2107  
2108  
2109  
2110  
2111  
2112  
2113  
2114  
2115  
2116  
2117  
2118  
2119  
2120  
2121  
2122  
2123  
2124  
2125  
2126  
2127  
2128  
2129  
2130  
2131  
2132  
2133  
2134  
2135  
2136  
2137  
2138  
2139  
2140  
2141  
2142  
2143  
2144  
2145  
2146  
2147  
2148  
2149  
2150  
2151  
2152  
2153  
2154  
2155  
2156  
2157  
2158  
2159  
2160  
2161  
2162  
2163  
2164  
2165  
2166  
2167  
2168  
2169  
2170  
2171  
2172  
2173  
2174  
2175  
2176  
2177  
2178  
2179  
2180  
2181  
2182  
2183  
2184  
2185  
2186  
2187  
2188  
2189  
2190  
2191  
2192  
2193  
2194  
2195  
2196  
2197  
2198  
2199  
2200  
2201  
2202  
2203  
2204  
2205  
2206  
2207  
2208